

Specifications

Maximum Capacity	220 g
Readability	0.01 mg
Auto Door	Included
Built-in Ionizer	Yes
Internal Calibration	AutoCal™ - Automatic
Minimum Weight (USP, 0.1%, typical)	20 mg
Draftshield	Included
Auxiliary Display Model	Available as an Accessory
Battery Life	Not Applicable
Communication	RS232 (Included); USB (Included); USB Host; Ethernet (Available as an Accessory)
Dimensions (HxLxW)	13.8 in x 15.5 in x 9.1 in (350 mm x 393 mm x 230 mm)
Display	Full-color 5.7 in VGA, touch screen

In-use cover	Included
Legal for Trade	No
Linearity ±	0.1 mg
Net Weight	7.5 kg
Pan Construction	Stainless Steel
Pan Size (HxØ)	3.14 in (80 mm)
Power	AC Adapter (Included)
Repeatability (typical)	0.015 mg
Stabilization Time	8 s
Tare Range	To capacity by subtraction
Units of Measurement	Gram; Kilogram; Carat; Grain; Ounce; Ounce Troy; Pennyweight; Momme; Tical; Mesghal; Tola; Custom
Working Environment	50°F – 86°F, 85%RH, non-condensing (10°C – 30°C, 85%RH, non-condensing)